

Date Revised: 02/22/2019

Supersedes: 06/21/2018

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name(s): Five Star® Grout

Five Star® Grout Red Five Star® Grout N

Synonyms: FSG, FS Grout

Product Use: For use in supporting machinery and equipment requiring precision

alignment.

Restrictions on Use: N/A

Manufacturer/Supplier Five Star Products, Inc.

60 Parrott

Shelton, CT 06484 USA

Phone #: 203-336-7900

Emergency Phone #: CHEM-TEL 1-800-255-3924

(Outside the U.S. 1-813-248-0585)

SECTION 2: HAZARD(S) IDENTIFICATION-GHS INFORMATION

Classification: Acute Oral Toxicity – Category 4

Skin Corrosion/Irritation – Category 1
Acute Toxicity – Dermal, Category 5
Sensitization – Dermal, Category 1
Eye Damage/Irritation – Category 1
Sensitization – Respiratory, Category 1

Specific Target Organ Systemic Toxicity (Single Exposure) - Cat 3

Carcinogenicity - Category 1A

Specific Target Organ Toxicity (Repeated Exposure) - Cat 2

Label Elements/Hazard

Pictograms:







Signal Word: Danger

Hazard Statements: H302 Harmful if swallowed

H313 May be harmful in contact with skin

H314 Causes severe skin burns and eye damage

H317 May cause an allergic skin reaction

H318 Causes serious eye damage

H334 May cause allergy or asthma symptoms or breathing difficulties if

inhaled

H335 May cause respiratory irritation



Date Revised: 02/22/2019

Supersedes: 06/21/2018

H350 May cause cancer

H373 May cause damage to organs through prolonged or repeated

exposure

Precautionary
Statements/Prevention:

P260 Do not breathe dust, fume, gas, mist, vapors, or spray

P264 Wash thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P272 Contaminated work clothing should not be allowed out of the

workplace

P280 Wear protective gloves, protective clothing, eye protection and

face protection

P284 Wear respiratory protection

Response: P330, 331 If swallowed: Rinse mouth. Do NOT induce vomiting

P361, 353 If on skin (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower

P340 If inhaled: Remove person to fresh air and keep comfortable for

breathing

P351, P338, P310 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P310 Immediately call a poison center or doctor

P333, P313 If skin irritation or rash occurs: Get medical

advice/attention.

P342, P310, P363 If experiencing respiratory symptoms: Call a poison

center or doctor. Wash contaminated clothing before reuse,

P363.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with applicable regional,

national, and local laws and regulations.

Hazards Not Otherwise

Classified:

Not applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS				
Hazardous Ingredient(s)	Common Name/Synonyms	CAS No.	% wt/wt	
Portland Cement*	Hydraulic cement	65997-15-1	45-60	
Quartz	Silicon Dioxide, Silica Sand	14808-60-7	40-55	

^{*} Portland Cement typically contains about 0.5 ppm of Cr(VI) which may affect sensitized individuals to dermatitis.



Date Revised: 02/22/2019

Supersedes: 06/21/2018

SECTION 4: FIRST AID MEASURES

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for

breathing.

If experiencing respiratory symptoms call poison center or doctor.

Eye Contact: If in eyes: Rinse cautiously with water for at least 30 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Immediately

call a poison center or doctor.

Skin Contact: If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower for at least 15 minutes. Immediately call a poison center or doctor if irritation develops. Wash contaminated clothing

before reuse.

Ingestion: If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a

poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth

to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Flammability and Explosion

Information: Not flammable or combustible by OSHA/WHMIS criteria.

Sensitivity to Mechanical

Impact: This material is not sensitive to mechanical impact.

Sensitivity to Static

Discharge: None

MEANS OF EXTINCTION

Suitable Extinguishing Media: Small Fire: Dry chemical, CO2, or water spray.

Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire-

control water for later disposal; do not scatter the material.

Unsuitable Extinguishing

Media: Not available

Product of Combustion: Non-combustible

Protection of Firefighters: As in any fire, wear self-contained breathing apparatus pressure-

demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



Date Revised: 02/22/2019

Supersedes: 06/21/2018

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures: Use personal protective equipment. Ensure adequate ventilation. Keep

people from spill. Avoid dust formation.

Personal Precautions: Avoid inhalation of dust. Do not get into eyes, on skin, or clothing.

Environmental Precautions: The environmental impact of this product has not been fully investigated.

Methods for Containment: Cover powder spill with plastic sheet or tarp to minimize spreading.

Collect this material into a disposal container by sucking or sweeping up.

Methods for Cleanup: Pick up and transfer to properly labeled containers.

Other Information: See Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Handling: Wear personal protective equipment. Ensure adequate ventilation. Avoid

dust formation. Do not breathe dust. Prevent contact with skin, eyes,

and clothing. Wash thoroughly after handling.

Storage: Keep containers tightly closed in a cool, dry, and well-ventilated place.

Store locked up.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	CAS No.	ACGIH TLV	OSHA PEL
Portland cement	65997-15-1	TWA: 1mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction TWA: 50 mppcf <1% Crystalline silica
Quartz**	14808-60-7	TWA: 0.025mg/m³ respirable fraction	TWA: 0.050 mg/m³ AL: 0.025 mg/m³

PEL: Permissible Exposure Limit TLV: Threshold Limit Value AL: Actionable Level

** Respirable(< 6 micron) fraction for product is < 0.1%.

Engineering Controls: Not normally required.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Eye/Face Protection: Tightly fitting safety goggles

Hand Protection: Impervious gloves. Impervious clothing.



Date Revised: 02/22/2019

Supersedes: 06/21/2018

Skin and Body Protection: Impervious gloves. Impervious clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA

approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance

with current local regulations.

General Hygiene Considerations:

Handle according to established industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES				
Appearance:	Gray, finely ground solid powder			
Color:	Gray			
Odor:	mILD			
Odor Threshold:	None			
Physical State:	Solid, powder			
pH:	12 when mixed with water			
Melting Point / Freezing Point:	> 1832°F (1000°C)			
Initial Boiling Point:	Not Applicable			
Boiling Point:	> 3632°F (2000°C)			
Flash Point:	Not Applicable			
Evaporation Rate:	Not Applicable			
Flammability (solid, gas):	Not Applicable			
Lower Flammability Limit:	Not Applicable			
Upper Flammability Limit:	Not Applicable			
Vapor Pressure:	Not Applicable			
Vapor Density:	Not Applicable			
Relative Density:	2.70 - 3.10			
Solubility:	Slight 0.2 - 0.5%			
Partition Coefficient: n-Octanol/Water:	Not Applicable			
Auto-ignition Temperature:	Not Applicable			
Decomposition Temperature:	Not Applicable			
Viscosity:	Not Applicable			
Percent Volatile, wt.%:	Not Applicable			
VOC Content, wt.%:	Not Applicable			



Date Revised: 02/22/2019

Supersedes: 06/21/2018

Density:	2.71 – 3.1 g/cc
Coefficient of Water/Oil Distribution:	Not Applicable

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under recommended storage conditions.

Possibility of Hazardous

Reactions: None under normal processing.

Conditions to Avoid: Exposure to water – product may harden on contact with water.

Incompatible Materials: Strong acids.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product information

Inhalation: Irritating to respiratory system. Irritating to mucous membranes.

Eye contact: Risk of serious damage to eyes.

Skin contact: Irritating to skin. May cause allergic skin reaction. May cause alkali

burns.

Ingestion: Harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Portland Cement	Not Available	Not Available	Not Available

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz	500 – 22,500 mg/kg (Rat)	Not Established	Not Established*

^{*}LCL50: 0.3 mg/m3 / 10Y (Human)

Symptoms related to the physical, chemical and

toxicological characteristics: No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization: May cause sensitization by skin contact.

Mutagenic Effects: No information available.



Date Revised: 02/22/2019

Supersedes: 06/21/2018

Carcinogenicity: The table below indicates whether each agency has listed any ingredient

as a carcinogen. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human

carcinogen (Group 1). May cause cancer by inhalation.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz	A2*	Group 1	Known	X

^{*}The presence of a minimal amount of crystalline silica is typical in the mineral admixture, the respirable fraction as a whole is less than 0.1% and anticipated usage would generate far less than 0.1% as a respirable quantity above exposure guidelines as noted in Section 8.

ACGIH: (American Conference of Governmental Industrial

Hygienists): A2 - Suspected Human Carcinogen

IARC: (International Agency

for Research on Cancer): Group 1 - Carcinogenic to Humans

NTP: (National Toxicity

Program): Known Carcinogen

OSHA: (Occupational Safety &

Health Administration): X - Present

Reproductive Toxicity: No information available.

STOT - single exposure: May cause respiratory irritation.

STOT - repeated exposure: Causes damage to organs through prolonged or repeated exposure if

inhaled. Lungs.

Chronic Toxicity: Inhalation overexposure to free crystalline silica may cause delayed lung

injury including silicosis, a disabling and potentially fatal lung disease.

Aspiration Hazard: No information available.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD 50 Oral: 500 mg/kg; Acute toxicity estimate

SECTION 12: ECOLOGICAL INFORMATION

Toxicity: The environmental impact of this product has not been fully

investigated.

Aquatic Toxicity: The environmental impact of this product has not been fully

investigated. Portland cement contains up to about 3-5% calcium

oxide.

Calcium Oxide (1305-78-8):

• 96 hour LC50 freshwater fish – Species: Cyprinus carpio =1070 mg/l

(static)



Date Revised: 02/22/2019

Supersedes: 06/21/2018

• Chronic 46 day NOEC freshwater fish – Species: Oreochromis niloticus juvenile (fledgling, hatchling, weanling) = 100 mg/l

Persistence and Degradability:

No information available.

Bio-accumulative Potential: Does not accumulate in organisms

Mobility in Soil: No further relevant information available

Ecotoxical Effects

Remark: No information available.

Additional Ecological

Information:

No information available.

General Notes: This statement was deduced from products with a similar structure or

composition. Due to available data on eliminability/decomposition and bio-accumulation potential prolonged term damage of the environment cannot be excluded. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Addition of water to cement creates an alkaline pH of between 12-13. Cured product is inert. Common to concrete construction around waterways, particular concern should be given to best practices to avoid/minimize spillage/discharge to the nearby environment as best as possible. In the case of significant spillage in confined or restricted areas, pH may

increase to a level toxic to fish and aquatic organisms.

PBT Assessment: Not Available

vPvB Assessment: Not Available

Other Adverse Effects: No further relevant information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Recommendation: This material as supplied is not a hazardous waste according to Federal

regulations (40CFR261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if

the material is processed or otherwise altered.

Uncleaned Packaging

Recommendation: Disposal must be made according to official regulations. Do not re-use

empty containers.

SECTION 14: TRANSPORT INFORMATION

US DEPARTMENT of TRANSPORTATION (DOT)

Proper Shipping Name: Not Regulated

Class: Not Applicable



Date Revised: 02/22/2019

Supersedes: 06/21/2018

UN #: Not Applicable

Packing Group: Not Applicable

CANADA Transportation of Dangerous Goods (TDG)

Proper Shipping Name: Not Regulated

Class: Not Applicable

UN #: Not Applicable

Packing Group: Not Applicable

Air Transport (ICAO-

IATA/DGR)

Proper Shipping Name: Not Regulated

Class: Not Applicable

UN #: Not Applicable

Packing Group: Not Applicable

Sea Transport (IMDG-

Code/GGVSee): Not Regulated

UN #: Not Applicable

Proper Shipping Name: Not Applicable

Class: Not Applicable

Packing Group: Not Applicable

Marine Pollutant: Not Applicable

Special Provision(s): Not Applicable

SECTION 15: REGULATORY INFORMATION

CHEMICAL INVENTORIES

US (TSCA): The components of this product are in compliance with the chemical

notification requirements of TSCA.

CANADA (DSL): The components of this product are in compliance with the chemical

notification requirements of NSN Regulations under CEPA, 1999.

U.S. FEDERAL REGULATIONS Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and

Title 40 of the CFR, Part 372.

UNITED STATES: This SDS has been prepared to meet the US OSHA Hazard Communication

Standard, 29 CFR 1910.1200

SARA 311/312 Hazard

Categories

Acute health hazard – Yes Chronic Health hazard – Yes

Page 9 of 10 | Document No. 12253 Rev E



Date Revised: 02/22/2019

Supersedes: 06/21/2018

Fire Hazard - No

Sudden Release of Pressure - No

Reactive Hazard - No

US STATE Right to Know Regulations

Chemical Name	NJ	MA	PA	IL	RI
Portland Cement	X	x	x		X
Quartz	X	X	X		X

California Prop 65:

This product contains the following Proposition 65 chemicals:

Chemical Name: Quartz, CAS No 14808-60-7, CA Prop. 65: Carcinogen

Chemical Name: Chromium, CAS No 18450-29-9, CA Prop 65: Birth defects or other reproductive harm

SECTION 16: OTHER INFORMATION

Health	Flammability	Physical Hazard	Personal Protection
1	0	1	E, X

Disclaimer:

This information is furnished without warranty of any kind, expressed or implied. Five Star Products, Inc. bases the information and recommendations in this document on data believed to be current and accurate.